





mSATA Solid State Drive

Supporting the next-generation Serial ATA interface and built around a powerful controller, Transcend's SATA III 6Gb/s mSATA SSD 370S delivers blazing fast performance and long-term reliability. The compact mSATA form factor makes it perfect for use in space-restricted portable devices such as Ultrabooks, tablet PCs, and slim servers.



Superior upgrade option

All the speed is back and even faster. By using SATA III 6Gb/s interface, DDR3 DRAM cache, and a powerful controller, the Transcend mSATA SSD 370S provides the ultra-fast transfer speeds of up to 530MB/s read and 400MB/s write, pursuing the great experience in faster boot time and application launching time.



Up to 256GB capacity

The mSATA SSD 370S ranges from 16GB to 256GB, giving you more options to suit your demand while storing large multimedia files and applications in faster speed.



Speed up loading times

Dedicated to maximizing high-performance computing, the mSATA SSD 370S features maximum 4K random file read 70,000 IOP that delivers incredibly short loading times and almost instant response for heavy graphics and multimedia applications.





mSATA Solid State Drive mSATA SSD 370S

Features

- mSATA form factor and SATA III 6Gb/s interface
- · Up to 530MB/s read; 400MB/s write
- · MLC NAND flash memory
- Built-in ECC (Error Correction Code) function and wear-leveling algorithm to ensure reliable data transfers
- Supports DevSleep ultra low power state, S.M.A.R.T., TRIM, and NCQ commands

Transcend

SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specifications

Specifications		
Appearance		
Dimensions	50.8 mm x 29.85 mm x 4.85 mm (2.00" x 1.18" x 0.19")	
Weight	8 g (0.28 oz)	
Interface		
Bus Interface	SATA III 6Gb/s	
Storage		
Flash Type	MLC NAND flash	
Capacity	16GB/32 GB/64 GB/128 GB/256 GB	
Operating Environmer	it	
Operating Temperature	0°C (32°F) ~ 70°C (158°F)	
Operating Voltage	3.3V±5%	
Performance		
Sequential Read/Write (CrystalDiskMark, max.)	Read: 530 MB/s	
	Write: 400 MB/s	
4K Random Read/Write (IOmeter, max.)	Read: 70,000 IOPS	
	Write: 70,000 IOPS	
Mean Time Between Failures (MTBF)	2,000,000 hour(s)	
Terabytes Written (Max.)	740 TB	
Drive Writes Per Day (DWPD)	2.5 (3 yrs)	
Note		
Speed may vary due to host hard	ware, software, usage, and storage capacity.	
Warranty		
Certificate	CE/FCC/BSMI/KC/RCM	
Warranty	Three-year Limited Warranty	

Ordering Information

16GB	TS16GMSA370S
32GB	TS32GMSA370S
64GB	TS64GMSA370S
128GB	TS128GMSA370S
256GB	TS256GMSA370S

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



mSATA SSDs Comparison	SATA III 6Gb/s mSATA SSD 370S	SATA III 6Gb/s mSATA SSD 230S
Appearance		
Dimensions (Max.)	50.8 mm x 29.85 mm x 4.85 mm (2.00" x 1.18" x 0.19")	
Weight (Max.)	8 g (0.28 oz)	9 g (0.32 oz)
Storage		
Flash Type	MLC NAND flash	3D NAND flash
Capacity	16GB ~ 256GB	64GB ~ 256GB
Operating Environment		
Operating Temperature	0°C (32°F) ~ 70°C (158°F)	
Performance Sequential Read/Write (CrystalDiskMark, max.)	Read: 320 MB/s Write: 400 MB/s	Read: 550 MB/s Write: 400 MB/s
4K Random Read/Write (IOmeter, max.)	Read: 70,000 IOPS Write: 70,000 IOPS	Read: 55,000 IOPS Write: 70,000 IOPS
Mean Time Between Failures (MTBF)	2,000,000 hour(s)	2,000,000 hour(s)
Terabytes Written (Max.)	740 TB	160 TB
Drive Writes Per Day (DWPD)	2.5 (3 yrs)	0.5 (3 yrs)
Warranty		
Warranty	Three-year Limited Warranty	
Technology		
TRIM & NCQ Command	\checkmark	\checkmark
S.M.A.R.T.	✓	\checkmark
DDR3 DRAM Cache	✓	\checkmark
Advanced Garbage Collection	<i>✓</i>	\checkmark
DevSleep Mode	\checkmark	✓
RAID Engine	-	✓
LDPC Coding	-	~

*Speed may vary due to host hardware, software, usage, and storage capacity.