




Transcend's SATA III 6Gb/s M.2 SSD 600S boasts ultra compact dimensions to address the high performance needs and strict size limitations of small form factor devices, best suited for Ultrabooks and thin, light notebooks. Featuring a powerful controller, exceptional transfer speeds, and MLC NAND flash memory, the M.2 SSD 600S easily handles everyday computing tasks as well as demanding multimedia applications, delivering steadfast reliability.




Perfect for your Ultrabook

Measured at just 60mm in length, the M.2 SSD 600S makes for an easy upgrade to your computer, taking up little space while giving it a much needed energy boost.



Superior transfer speeds

Transcend's M.2 SSD 600S reaches incredible read and write speeds of up to 530MB/s and 400MB/s. When used as a cache, the M.2 SSD 600S provides 1.5 times faster boot time than conventional hard drives.



Store more in less space

The M.2 form factor enables expansion and integration of functions onto a single form factor module solution. M.2 SSDs include a smaller form factor but with larger capacities than that of mSATA and half-slim SSDs.





SATA III M.2 Solid State Drive

M.2 SSD 600S

Features

- · Space-saving M.2 Type 2260 form factor
- · Up to 256GB storage capacity
- · Up to 530 MB/s read; 400 MB/s write
- MLC NAND flash memory and DDR3 DRAM cache
- Supports DevSleep ultra low power state,
 S.M.A.R.T., TRIM, and NCQ commands

Transcend

SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specifications

Appearanc	E
-----------	---

Dimensions	60.0 mm x 22.0 mm x 3.58 mm (2.36" x 0.87" x 0.14")
Weight	7 g (0.25 oz)

Interface

Bus Interface SATA III 6Gb/s

Storage

Flash Type MLC NAND flash
Capacity 32 GB/64 GB/128 GB/256 GB

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	3.3V±5%

Performance

Sequential Read/Write (CrystalDiskMark)	Read: 530 MB/s
	Write: 400 MB/s
4K Random Read/Write	Read: 70,000 IOPS
(IOmeter)	Write: 70,000 IOPS
Mean Time Between Failure (MTBF)	s 2,000,000 hour(s)
Terabytes Written	740 TB
Drive Writes Per Day (DWPD)	2.5 (3 yrs)

Note

Speed may vary due to host hardware, software, usage, and storage capacity.

Warranty

Certificate	CE/FCC/BSMI/KC/RCM
Warranty	Three-year Limited Warranty

Ordering Information

32GB	TS32GMTS600S
64GB	TS64GMTS600S
128GB	TS128GMTS600S
256GB	TS256GMTS600S

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



SATA III M.2 SSDs Comparison







SATA III 6Gb/s M.2 SSD 600S



SATA III 6Gb/s

	M.2 SSD 400S	M.2 SSD 600S	M.2 SSD 800S
Appearance			
Dimensions	42.0 mm x 22.0 mm x 3.58 mm (1.65" x 0.87" x 0.14")	60.0 mm x 22.0 mm x 3.58 mm (2.36" x 0.87" x 0.14")	80.0 mm x 22.0 mm x 3.58 mm (3.15" x 0.87" x 0.14")
Weight	5 g (0.18 oz)	7 g (0.25 oz)	9 g (0.32 oz)
Storage			
Flash Type		MLC NAND flash	
Capacity	32GB ~ 256GB	32GB ~ 256GB	32GB ~ 512GB
Operating Environment			
Operating Temperature		0°C (32°F) ~ 70°C (158°F)	
Performance			
Sequential Read/Write (CrystalDiskMark)	Read: 530 MB/s Write: 400 MB/s	Read: 530 MB/s Write: 400 MB/s	Read: 530 MB/s Write: 460 MB/s
4K Random Read/Write (IOmeter)	Read: 70,000 IOPS Write: 70,000 IOPS	Read: 70,000 IOPS Write: 70,000 IOPS	Read: 70,000 IOPS Write: 75,000 IOPS
Mean Time Between Failures (MTBF)		2,000,000 hour(s)	
Terabytes Written (TBW)	740 TB	740 TB	1,480 TB
Drive Writes Per Day (DWPD)		2.5 (3 yrs)	
Warranty			
Warranty		Three-year Limited Warranty	
Technology			
TRIM & NCQ Command	✓	✓	✓
S.M.A.R.T.	~	~	✓
DDR3 DRAM Cache	✓	✓	✓
Advanced Garbage Collection	✓	✓	✓
DevSleep Mode	✓	✓	✓
RAID Engine	-	-	-
LDPC Coding	-	-	-

^{*}Speed may vary due to host hardware, software, usage, and storage capacity.